

ARTICLE 2. STREETS

- 15-201. **SAME; UNLAWFUL ACTS.** It shall be unlawful for any person, except those having authority from the city or any officer thereof to throw down, interfere with or remove any barriers, barricades, or lights placed in any street to guard and warn the traveling public of any construction work thereon or adjacent thereto. (Code 1997)
- 15-202. **ALTERING DRAINAGE.** No person shall change or alter any gutter, storm sewer, drain or drainage structure which has been constructed, or is being lawfully maintained or controlled by the city unless such change or alteration has been authorized or directed by the governing body. (Code 1997)
- 15-203. **UNFINISHED PAVEMENT.** No person shall walk upon, drive or ride over or across any pavement, sidewalk or incomplete grading which has not been opened for traffic. (Code 1997)
- 15-204. **USING STREETS.** (a) No person shall occupy any portion of any street, alley or sidewalk for the purpose of temporarily storing building materials without first obtaining a permit for such temporary use from the governing body.
- (b) No person may use any portion of any sidewalk or street right-of- way for the purpose of displaying or offering for sale wares, goods, merchandise or other items. Nothing in this article, however, shall be construed as prohibiting the city governing body from temporarily waiving the prohibition of this subsection in connection with community promotions or community-wide celebrations when such waiver is considered to be in the best interest of the city. (Code 1997)
- 15-205. **DANGEROUS OBJECTS IN.** It shall be unlawful for any person to place, throw or cause to be placed or thrown in or on any street, alley, sidewalk or other public grounds of the city, any glass, tacks, nails, bottles, wire or other dangerous objects that might wound any person or animal, or cut or puncture any pneumatic tire while passing over the same. (Code 1997)
- 15-206. **PETROLEUM PRODUCTS IN STREETS.** It shall be unlawful for any person, firm or corporation to deposit or throw any waste oil, fuel oil, kerosene, gasoline or other products of petroleum or any acids into or upon any street or public grounds of the city, or willfully to permit the same to be spilled, dripped or otherwise to come into contact with the surface of any street, alley, or sidewalk within the city. (Code 1997)

- 15-207. **DISCHARGING WATER ON STREETS.** It shall be unlawful for any person, firm or corporation to throw or discharge water into any ditch, street, avenue or alley in the city or to cause any water to stand or form pools or to flow in a stream thereon. This section shall not apply to persons cleaning or flushing such streets, avenues or alleys under the authority of the governing body, nor to members of the fire department. (Code 1997)
- 15-208. **HAULING LOOSE MATERIAL.** It shall be unlawful to haul over the streets or alleys of this city any loose material of any kind except in a vehicle so constructed or maintained as to prevent the splashing or spilling of any of the substances therein contained upon the streets or alleys. (Code 1997)
- 15-209. **STREET AND ROADWAY EXCAVATIONS.** (a) Concrete Pavement Repair Requirements: Pavement shall be removed and replaced by panels. Any trenching shall be completed within the panel removed with the trench being a minimum of 12 inches from the edge of the panel. If applicable, any excavation should be filled with sand to one foot over the pipe and then backfilled to the bottom of the pavement with flowable fill. The new panel will be installed using 4500 psi concrete with 620 lbs. of cement and a minimum of 30 percent rock and have a maximum slump of four inches. The concrete shall be installed, vibrated and finished to match the existing pavement. The new panel will be doweled into the existing pavement along the street centerline. The new pavement will match the existing pavement thickness, but not less than six inches in depth. The new pavement will have 6X6-W4xW4 welded wire fabric incorporated into the pavement (58 lbs./sq.ft.) and the WWF shall be located in the top 1/3 of the pavement. Saw all joints 1/4 inch wide by two inches deep and seal with hot tar similar to what is currently being used by the city.
- (b) Asphalt Pavement Repair Requirements: Pavement shall be removed and replaced to a width two feet wider than the trench (12 inches beyond each side of the trench). If applicable, any excavation should be filled with sand to one foot over the pipe and then backfilled to the bottom of the pavement with flowable fill. The repair will be installed using cold or hot mix asphalt similar to the Grant County mix currently in use. The asphalt shall be installed, compacted and finished to match the existing pavement. The new pavement will match the existing pavement thickness, but not less than six inches in depth.
(Ord. 1066, Sec. 1)